



“ Air Hangat Setiap Saat,
Harga Bersahabat “

WIKAWH ELECTRIC WATER HEATER

DISTRIBUTOR/AGEN :



Contact Us

Kantor dan Pabrik

Head office and Factory

Pabrik Wika Industri Energi

Kawasan Industri WIKAWH Bogor

(KIW-Bogor)

Jl. Raya Narogong Km.26,

Cileungsi, Bogor, 16820

T: (021) 86863293

F: (62-21) 86863294

E: info@wikaenergi.com

Manufactured by:



@wikawaterheater.id

www.wikaenergi.com



Certified Company
Cert. No. 18 00 A 20007



Certified Company
Cert. No. 18 04 A 20002



Certified Company
Certified No. 03 14 A 20002



AIR HANGAT SETIAP SAAT

Dengan desain baru yang lebih futuristik dengan cover plastik dan konsumsi daya yang lebih kecil (200 watt), WIKA Electric Water Heater memberikan kemudahan dalam mendapatkan air panas untuk mandi yang lebih praktis dan ekonomis.

Dibuat dengan material dan komponen terbaik, WIKA EWH dilengkapi dengan penerapan sistem manajemen mutu ISO 9001:2008 yang membuat produk yang terjamin kualitasnya.

PRINSIP KERJA

Pemanas air tenaga listrik dengan sistem manajemen energi yang dapat menjamin ketersediaan air panas dengan daya rendah dan hemat energi.

KEUNGGULAN



Blue Enamel Coating



Thermal Cut-Off



Polyurethane Insulation



Konsumsi daya rendah



High Precision Thermostat



Anti Korosi karena menggunakan Magnesium Anode



Nilai Investasi Rendah



Temperature Control Knob



Rasa aman karena terdapat (ELCB, Safety Valve & Thermal Cut-out)



Layanan purna jual mudah ditemui, tersebar diseluruh Indonesia, selalu siap membantu



ET 15BC01



ET 30BC01

DESCRIPTION	SPESIFICATION	
	ET 15BC01	ET 30BC01
Model	ET 15BC01	ET 30BC01
Capacity	15 Liter	30 Liter
Rated Power	200 Watt	300 Watt
Rated Voltage	220 Volt	
Rated Current	1 A	1.5 A
Max. Working Temperature	75 °C	
Max. Water Pressure	0.8 MPa	
Temperature Cutting	93 °C	
IP Rating	IPX4	
Product Size (L x W x H)	415 x 415 x 400 mm	435 x 435 x 392 mm
Packaging Size (L x W x H)	450 x 445 x 445 mm	480 x 500 x 470 mm
Product Feature	1. Upper sink unvented type 2. SPCC steel tank, with glasslined Enamel Coating, 10 bar standing pressure 3. Heating efficient, 20 mm seamless injected foaming 4. Anti-proof, anti-corrosion design 5. Mechanical 75°C thermostat and 93°C thermal cut 6. 8 bar safety valve with G 1/2" inlet/outlet 7. Space saving wall mounting 8. Thermal & heating indicator 9. RCD plug option	